

SELF DRILLING SCREW

AVAILABLE MATERIALS

- High strength steel, hardened tip, Ruspert coating

FEATURES/ADVANTAGES

- Both hex head and Phillips pan head available
- Carbon steel bodies with hardened cutting tip
- 1000 hour Ruspert coating for corrosion resistance



HEX HEAD WASHER ORDER DETAIL

| Order Code | Description | Point Size | Box Qty. |
|------------|---------------|------------|----------|
| 82108A2 | 8-18 x 1/2 | #2 Point | 6,500 |
| 82108C2 | 8-18 x 3/4 | #2 Point | 4,000 |
| 82108E2 | 8-18 x 1 | #2 Point | 2,500 |
| 82110A3 | 10-16 x 1/2 | #3 Point | 4,000 |
| 82110B3 | 10-16 x 5/8 | #3 Point | 3,000 |
| 82110C3 | 10-16 x 3/4 | #3 Point | 3,000 |
| 82110E3 | 10-16 x 1 | #3 Point | 2,000 |
| 82110G3 | 10-16 x 1-1/2 | #3 Point | 1,500 |
| 82110H3 | 10-16 x 2 | #3 Point | 1,000 |
| 82112C3 | 12-14 x 3/4 | #3 Point | 6,500 |
| 82112E3 | 12-14 x 1 | #3 Point | 5,300 |
| 82112H3 | 12-14 x 2 | #3 Point | 2,800 |
| 82112I3 | 12-14 x 2-1/2 | #3 Point | 1,900 |
| 82112J3 | 12-14 x 3 | #3 Point | 1,500 |



PHILLIPS PAN HEAD ORDER DETAIL

| Order Code | Description | Point Size | Box Qty. |
|------------|-------------|------------|----------|
| 82208A2 | 8-18 x 1/2 | #2 Point | 16,000 |
| 82208C2 | 8-18 x 3/4 | #2 Point | 13,000 |
| 82208E2 | 8-18 x 1 | #2 Point | 10,000 |

HVAC SCREW #8-36 X 1/2" HHWF - 1/4" DRIVE

AVAILABLE MATERIALS

- High strength steel, zinc plated
- available in economical bulk packs only

FEATURES/ADVANTAGES

- Sharp pointed, fine thread screw for use in sheet metals of several gauges
- No pre drilling is needed as the combination of a heat treated, sharp point and aggressive starting threads with fine thread up the shank provides a positive threading, chip free hole.
- The sharp point provides positive, fast starts in sheet metal.
- The fine thread up the shank rolls the material back instead of cutting chips that corrode quickly and cause a rattle in ductwork where vibration is present.
- The rolled material creates a larger bearing surface creating a more positive hold.
- The fine thread also provides better clamping forces on thinner materials.
- Heat treated to provide a hardened, sharp point and excellent thread cutting capabilities.
- The washer face has anti-backing serrations to keep it in place in harsh, vibratory conditions.

ORDER DETAIL

| Order Code | Box Qty. |
|------------|----------|
| 82108AOS | 1,000 |
| 82108AOM | 7,500 |
| 82108AOL | 15,000 |

